



**TRIJICON**  
**TARS®**

## “REACH-OUT-AND-TOUCH-‘EM” TECHNOLOGY

The Trijicon TARS® (Tactical Advanced Rifle Scope) is a rugged, variable-power riflescope with the precise adjustability that long-range shooting demands. It features a first focal plane reticle with 10 illumination settings, including two for night vision. Oversized target adjusters feature 120 MOA/36 MIL total elevation and windage adjustments and 30 MOA/10 MIL adjustments per revolution as well as a mechanism to prevent unintentional adjuster rotation. Combined with an elevation return-to-zero feature, the Trijicon TARS allows for rapid zeroing on a target, no matter the distance.

### MODELS



3-15x50

## FEATURES

### PREMIUM GLASS

Multi-coated lenses provide superior clarity and light-gathering capabilities with zero distortion.

### FIRST FOCAL PLANE RETICLE

Reticle subtensions remain true at any magnification.

### RETURN-TO-ZERO (ELEVATION)

Elevation adjuster features a stop mechanism which allows the user to quickly return to a pre-set zero.

### AIRCRAFT-GRADE, HARD-ANODIZED ALUMINUM BODY

Thick-walled, MIL-spec, rugged construction for increased strength and protection against the toughest environments.

### CONSTANT EYE RELIEF

3.3 in. of eye relief stays constant throughout the entire magnification range, eliminating the need to reposition the head when making magnification adjustments.

### SIDE-FOCUS PARALLAX COMPENSATION

From 40 yards to infinity.

### HYDROPHOBIC COATING

On exposed objective and ocular lenses to prevent moisture buildup.

### ZERO FORWARD EMISSION

The illuminated reticle does not project any illumination from the objective lens.

### WATERPROOF TO 20 METERS (66 ft.)

Dry-nitrogen-filled to eliminate fogging.

### LIMITED LIFETIME WARRANTY

Electronics are warranted for 5 years from date of original manufacture.



## SPECIFICATIONS

SYSTEM	3-15X50
MAGNIFICATION	3 – 15x
OBJECTIVE LENS	50mm
FOCAL PLANE	First
EYE RELIEF	3.3 in. Constant 83.8mm Constant
EXIT PUPIL	0.66 – 0.13 in. 16.8 – 3.3mm
FIELD OF VIEW (DEGREES)	7.15° – 1.43°
FIELD OF VIEW	37.4 – 7.5 ft. @ 100 yds. 12.5 – 2.5m @ 100m
ADJUSTMENTS	¼ MOA Per Click .01 MIL Per Click
ADJUSTMENT RANGE (ELEVATION AND WINDAGE)	MOA: 120 MOA Total Travel (30 MOA per Revolution) MIL: 36 MIL Tested Travel (10 MIL per Revolution)
PARALLAX	40 yds. to Infinity
DIMENSIONS (L X W X H)	13.9 x 3.8 x 3.5 in. (w/o Sunshade) 353 x 97 x 89mm 16.9 x 3.8 x 3.5 in. (w/ Sunshade) 429 x 97 x 89mm
WEIGHT	47 oz. (w/o Sunshade) 1332g 51 oz. (w/ Sunshade) 1446g
ILLUMINATION SOURCE	LED Powered by a CR2032 Lithium Battery
BATTERY LIFE	175 Hours on Setting 6* (Day 1) – Constant On
BRIGHTNESS SETTINGS	10 Total Settings: NV 1, NV 2, Tritium Equivalent, Dusk/Dawn 1, Dusk/Dawn 2, Day 1, Day 2, Day 3, Day 4, Intense Sun
TUBE DIAMETER	34mm

\*Sunshade not included.

### 3-15x50




34mm Riflescope with MIL Adjusters, JW MIL-Square Reticle and Flip Caps

Black: ■ TARS103

34mm Riflescope with MIL Adjusters, Duplex Reticle and Flip Caps

Black: ■ TARS104



JW MIL-Square



Duplex