

# ACCURACY INTERNATIONAL AX308

#### CALIBER

.308 Winchester (short action)

## WEIGHT

6.2kg (13.7lb) with standard rail setup, empty magazine, no scope, 24" barrel, tactical muzzle brake

### DIMENSIONS

Full length: 1155mm x 180mm x 100mm Stock folded: 940mm x 180mm x 105mm with 24" barrel, tactical muzzle brake

#### FEATURES

Proofed steel action featuring Al's patent pending Quickloc quick release barrel system, bolted and bonded to aluminum chassis

20 MOA STANAG 4694 / Mil Std 1913 action and forend rail

6 lug, 60° bolt with AI combat proven leaf spring extractor

3 position safety

Two stage trigger adjustable for trigger weight between 1.5 and 2kg

Detachable 10-round double stack magazine - can also be top loaded though the rifle ejection port

Left side magazine port cut out for ease of magazine insertion

#### BASE MODEL

Right side folding stock over bolt

Adjustable cheekpiece

Adjustable buttpad with spacers

Pistol grip

Flush cup sling attachment points

20 MOA STANAG 4694 / Mil Std 1913 action rail and 13" forend tube and rail

Double chamber standard muzzle brake

1 x 140mm plain accessory rail

2 x 80mm flush cup accessory rails

#### User manual

1 x 10 round double stack magazine

#### COLORS

AX rifles benefit from a Cerakote ceramic polymer firearm coating. Choose from: High performance in three unique AI colors Elite ultra high performance for unrivalled durability CARK EARTH ELITE SAND ELITE MIDNIGHT

# FACTORY BARREL OPTIONS

20"/24"/26" 1 in 12" twist, stainless steel, plain threaded for muzzle brake

# OPTIONS

Tactical threaded double chamber muzzle brake for AI suppressor

#### ACCESSORIES

STANAG 4694 / Mil std 1913 accessory rails to attach to Al's patented KeySlot™ mounting system

## Bipods

Rear butt spike

Al bipod and Harris bipod mount

Handstop with sling loop and flush cup

Suppressor

Slings

Transit cases

Cleaning kits



Accuracy International of North America Inc. T: 540-368-3108 F: 540-368-3109 E: info@accuracyinternational.us www.accuracyinternational.us @Accuracy International2017. All rights reserved, specification may be subject to change without notice

31

0.0

