



UPC See price sheet

5.56 x 45mm NATO (.223 REM) CALIBER

CHAMBER E2 Dual Extraction Technology

ACTION Semi-auto, short-stroke gas piston system

WEIGHT 7.0 lbs / 3.18kg (empty)

BARREL 16.5" / 36.83cm match-grade nitride heat-treated

RIFLING 1:8, 1/2x28 barrel threads

LENGTH 34.0" / 86.36cm (collapsed)

FINISH Black anodized, NP3, burnt bronze, tungsten

GAS BLOCK 5-position adjustable

HANDGUARD 14.5" M-LOK MRR free-floating rail

MUZZLE DEVICE Triple port muzzle brake

> TRIGGER 4.5 lb POF-USA drop-in trigger system

with KNS anti-walk pins

FURNITURE Mission First Tactical

ACCURACY MOA with proper ammo and shooter ability

FIRE CONTROL Gen4 billet lower receiver

> Ambidextrous bolt release Ambidextrous safety selector Ambidextrous bolt catch Ambidextrous magazine release

MAINTENANCE Remove gas plug to clean gas block and piston

components without removing handguard. No tools required. Standard receiver/carrier group field strip

procedures

INCLUDES High phosphate nickel coated bolt carrier group

Chrome plated bolt 6-position anti-tilt buffer tube Magpul 20-round magazine Teflon receiver tension screws







